

Art Unit: ***

CLMPTO

11/30/2001

TD

05980210-1-217

1. A distributed printing control apparatus connecting with a plurality of printers, said distributed printing control apparatus distributing
5 print data of interest, which is generated by an application program and is to be printed, into said plurality of printers, converting the distributed print data into output data suitable for each of said printers via a printer driver provided for said each printer, and transmitting the converted output data to said each printer, said distributed printing control apparatus comprising:
- 10 a virtual printer driver storage module that stores therein a virtual printer driver for specifying information on a virtual printer; and
- an intermediate print data generation module that executes the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program,
- 15 wherein the obtained intermediate print data is used as the print

Art Unit: ***

data of interest.



2. A distributed printing control apparatus in accordance with claim 1,
whercin the virtual printer driver specifies information with regard to a
20 highest-performance printer among all available printers as destinations of
distribution.

3. A distributed printing control apparatus in accordance with claim 2,
said distributed printing control apparatus further comprising:
25 a performance information collection module that collects information
with regard to performances of all said available printers as the destinations

of distribution from printer drivers individually provided for said available
printers; and

a highest performance selection module that selects a highest
performance among the performances of all said available printers collected
5 by said performance information collection module.

Art Unit: ***

4. (Amended) A distributed printing control apparatus in accordance with claim 1, said distributed printing control apparatus further comprising: a virtual printer printing information setting module that displays an input window on a display device and sets various pieces of information required for printing with said virtual printer, based on input data from an input device like a mouse and a keyboard.

15 5. A distributed printing control apparatus in accordance with claim 4, said distributed printing control apparatus further comprising:

an information transmission module that causes at least part of the various pieces of information set by said virtual printer printing information setting module to undergo a series of processing carried out by each printer
20 driver.

6. (Amended) A distributed printing control apparatus in accordance with claim 4, said distributed printing control apparatus further comprising: a real printer printing information setting module that is individually provided for each of said plurality of printers connected to said distributed printing control apparatus to set various pieces of information required for printing with said each printer; and a display control module that displays a display window on said display device, the display window including a plurality of icons for individually activating said real printer printing information setting modules and an icon for activating said virtual printer printing information setting module.

Art Unit: ***

7. (Amended) A distributed printing control apparatus in accordance with claim 1, said distributed printing control apparatus further comprising: a distribution information setting module that displays an input window for distribution of the print data and sets various pieces of information required for distributing the print data into said plurality of printers, based on the input data from said input device; and a print data distribution module

8. A distributed printing control apparatus in accordance with claim 7, wherein one of the various pieces of information required for distributing the print data into said plurality of printers restricts a destination of distribution of the print data to a printer included in a specific group selected among said plurality of printers connected to said distributed printing control apparatus.

9. (Amended) A distributed printing control apparatus in accordance with claim 1, wherein the intermediate print data obtained by said intermediate print data generation module is temporarily registered as an intermediate print file in an external storage device.

10. (Amended) A distributed printing control apparatus in accordance with claim 1, wherein said plurality of printers are connected to said distributed printing control apparatus via a computer network.

Art Unit: ***

09980210-13004

11. A distributed printing control method that distributes print data
10 of interest, which is generated by an application program and is to be printed,
into a plurality of printers, converts the distributed print data into output
data suitable for each of said printers via a printer driver provided for said
each printer, and transmits the converted output data to said each printer,
said distributed printing control method comprising the steps of:
- 15 (a) providing in advance a virtual printer driver for specifying
information on a virtual printer in a storage device; and
- (b) executing the virtual printer driver to obtain intermediate print
data adequate for said virtual printer from said application program,
wherein the obtained intermediate print data is used as the print
20 data of interest.

12. A distributed printing control method that distributes print data
of interest, which is generated by an application program and is to be printed,
into a plurality of printers, converts the distributed print data into output
25 data suitable for each of said printers via a printer driver provided for said
each printer, and transmits the converted output data to said each printer,

Art Unit: ***

said distributed printing control method comprising at least one step corresponding to the structure of a distributed printing control apparatus in accordance with any one of claims 2 to 10.

5 13. A computer readable recording medium in which a computer program used in a distributed printing control apparatus is recorded, said distributed printing control apparatus connecting with a plurality of computers, distributing print data of interest, which is generated by an application program and is to be printed, into a plurality of printers,
10 converting the distributed print data into output data suitable for each of said printers via a printer driver provided for said each printer, and transmitting the converted output data to said each printer, said computer program causing a computer to attain the functions of:

(a) providing in advance a virtual printer driver for specifying
15 information on a virtual printer in a storage device; and

(b) executing the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program and using the obtained intermediate print data as the print data of interest.

20 14. A computer readable recording medium in accordance with claim 13, wherein the virtual printer driver specifies information with regard to a highest-performance printer among all available printers as destinations of distribution.

25 15. A computer readable recording medium in accordance with claim 14, wherein said computer program further causes the computer to attain the

T. 09/980,210

Art Unit: ***

functions of:

(c) collecting information with regard to performances of all said available printers as the destinations of distribution from printer drivers individually provided for said available printers; and

5 (d) selecting a highest performance among the performances of all said available printers collected by said function (c).

16. (Amended) A computer readable recording medium in accordance with claim 13, wherein said computer program further causes the computer to attain the function of: (c) displaying an input window on a display device and setting various pieces of information required for printing with said virtual printer, based on input data from an input device like a mouse and a keyboard.

11000000

15 17. A computer readable recording medium in accordance with claim 16, wherein said computer program further causes the computer to attain the function of:

causing at least part of the various pieces of information set by said function (e) to undergo a series of processing carried out by each printer
20 driver.

18. (Amended) A computer readable recording medium in accordance with claim 16, wherein said computer program further causes the computer to attain the functions of: (f)

Art Unit: ***

setting various pieces of information required for printing with each of said plurality of printers connected to said distributed printing control apparatus, said function (f) being individually set for said each printer; and (g) displaying a display window on said display device, the display window including a plurality of icons for individually activating said functions (f) and an icon for activating said function (e).

19. (Amended) A computer readable recording medium in which a computer program used in a distributed printing control apparatus is recorded, said distributed printing control apparatus connecting with a plurality of computers, distributing print data of interest, which is generated by an application program and is to be printed, into a plurality of printers, converting the distributed print data into output data suitable for each of said printers via a printer driver provided for said each printer, and transmitting the converted output data to said each printer, said computer program causing a computer to attain at least one function corresponding to the structure of a distributed printing control apparatus in accordance with claim 7.

20. A computer program that is used in a distributed printing control apparatus, said distributed printing control apparatus connecting with a plurality of computers, distributing print data of interest, which is generated by an application program and is to be printed, into a plurality of printers, converting the distributed print data into output data suitable for each of said printers via a printer driver provided for said each printer, and transmitting the converted output data to said each printer, said computer program causing a computer to attain the functions of:

PT: 01203650

Art Unit: ***

09980210-113001

21. A distributed printing control apparatus that distributes print data of interest, which is generated by an application program and is to be printed, into a plurality of printers and outputs the distributed print data to
10 each of said plurality of printers via a printer driver corresponding to a type of said each printer, said distributed printing control apparatus comprising:

a virtual printer driver storage module that, when said plurality of printers are of an identical type, stores therein a virtual printer driver for specifying information on the identical type of said printers as information
15 with regard to a virtual printer;

an intermediate print data generation module that executes the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program;

a print data allocation module that allocates the intermediate print
20 data to said plurality of printers; and

an output data control module that transmits the intermediate print data respectively to said plurality of printers according to the allocation by said print data allocation module without any data conversion by the
corresponding printer driver.

25

22. A distributed printing control apparatus in accordance with claim

21, wherein a predetermined unit of the allocation of the intermediate print data by said print data allocation module is each page of a document expressed by print data.

Art Unit: ***

23. (Amended)

23. (Amended) A distributed printing control apparatus in accordance with claim 21, wherein the intermediate print data obtained by said intermediate print data generation module is temporarily registered as an intermediate print file in an external storage device.

10

24. A distributed printing control apparatus in accordance with claim 23, said distributed printing control apparatus reading the intermediate print file registered in said external storage device in response to an external command and re-executing distributed printing of the intermediate print data in the intermediate print file with said plurality of printers.

15

25. A distributed printing control apparatus in accordance with claim 24, wherein said print data allocation module and said output data control module are activated again to attain the re-execution of the distributed printing.

26. (Amended)

26. (Amended) A distributed printing control apparatus in accordance with claim 21, said distributed printing control apparatus further comprising: a performance information collecting module that collects information regarding performances of each of said plurality of printers from a printer driver provided for said each printer; and an identity decision module that determines that said plurality of printers are of the identical type, based on the performances of said plurality of printers collected by said performance information collecting module.

Art Unit: ***

27. (Amended) A distributed printing control apparatus in accordance with claim 21, said distributed printing control apparatus further comprising: a distribution information setting module that displays an input window for distribution of the print data and sets various pieces of information required for distributing the print data into said plurality of printers, based on input data from an input device, wherein said print data allocation module allocates the intermediate print data, based on the various pieces of information set by said distribution information setting module.

10

28. A distributed printing control apparatus in accordance with claim 27, wherein one of the various pieces of information required for distributing the print data into said plurality of printers restricts a destination of distribution of the print data to a printer included in a specific group selected among said plurality of printers connected to said distributed printing control apparatus.

20

29. (Amended) A distributed printing control apparatus in accordance with claim 27, wherein the intermediate print data obtained by said intermediate print data generation module is specified as an intermediate print file and is temporarily registered, together with the various pieces of information set by said distribution information setting module, in an external storage device.

30. (Amended) A distributed printing control apparatus in accordance with claim 21, wherein at least one of said plurality of printers is connected to said distributed printing control apparatus via a computer network.

09/980,210-1,337

Art Unit: ***

31. A distributed printing control apparatus that distributes print
10 data of interest, which is generated by an application program and is to be
printed, into a plurality of printers and outputs the distributed print data to
each of said plurality of printers via a printer driver corresponding to a type
of said each printer, said distributed printing control apparatus comprising:
- a virtual printer driver storage module that specifies information on a
15 virtual printer, and when said plurality of printers are of an identical type,
stores therein a virtual printer driver for specifying information on the
identical type of said printers;
 - an intermediate print data generation module that executes the
virtual printer driver to obtain intermediate print data adequate for said
20 virtual printer from said application program;
 - a print data allocation module that allocates the intermediate print
data to said plurality of printers;
 - an identity decision module that determines whether or not said
plurality of printers are of the identical type; and
 - 25 an output data control module that, when it is determined that said
plurality of printers are of the identical type, transmits the intermediate
print data respectively to said plurality of printers according to the allocation
by said print data allocation module without any data conversion by the
corresponding printer driver, and when it is determined that said plurality of
printers are not of the identical type, transmits the intermediate print data
5 respectively to said plurality of printers according to the allocation by said
print data allocation module with data conversion by the corresponding
printer driver.

Art Unit: ***

109900010-1-01200560

10 32. A distributed printing control method that distributes print data of interest, which is generated by an application program and is to be printed, into a plurality of printers and outputs the distributed print data to each of said plurality of printers via a printer driver corresponding to a type of said each printer, said distributed printing control method comprising the steps of:

15 (a) when said plurality of printers are of an identical type, providing in advance a virtual printer driver for specifying information on the identical type of said printers as information with regard to a virtual printer in a storage device;

(b) executing the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program;

20 (c) allocating the intermediate print data to said plurality of printers; and

(d) transmitting the intermediate print data respectively to said plurality of printers according to the allocation in said step (c) without any data conversion by the corresponding printer driver.

11

33. (Amended) A distributed printing control method that distributes print data of interest, which is generated by an application program and is to be printed, into a plurality of printers and outputs the distributed print data to each of said plurality of printers via a printer driver corresponding to a type of said each printer, said distributed printing control method comprising at least one step corresponding to the structure of a distributed printing control apparatus in accordance with claim 22.

Art Unit: ***

09/980,210
U.S. PAT. & T.M. OFFICE

34. A distributed printing control method that distributes print data
10 of interest, which is generated by an application program and is to be printed,
into a plurality of printers and outputs the distributed print data to each of
said plurality of printers via a printer driver corresponding to a type of said
each printer, said distributed printing control method comprising the steps of:

(a) specifying information on a virtual printer, and when said
15 plurality of printers are of an identical type, providing in advance a virtual
printer driver for specifying information on the identical type of said printers
in a storage device;

(b) executing the virtual printer driver to obtain intermediate print
data adequate for said virtual printer from said application program;

20 (c) allocating the intermediate print data to said plurality of printers;

(d) determining whether or not said plurality of printers are of the
identical type; and

(e) when it is determined that said plurality of printers are of the
identical type, transmitting the intermediate print data respectively to said
25 plurality of printers according to the allocation in said step (c) without any
data conversion by the corresponding printer driver, and when it is

determined that said plurality of printers are not of the identical type,
transmitting the intermediate print data respectively to said plurality of
printers according to the allocation in said step (c) with data conversion by
the corresponding printer driver.

Art Unit: ***

09980210-113001

35. A computer readable recording medium in which a computer program used in a distributed printing control apparatus is recorded, said distributed printing control apparatus distributing print data of interest, which is generated by an application program and is to be printed, into a plurality of printers of an identical type and outputting the distributed print data to each of said plurality of printers via a printer driver provided for said each printer, said computer program causing a computer to attain the functions of:

(a) when said plurality of printers are of the identical type, providing in advance a virtual printer driver for specifying information on the identical type of said printers as information with regard to a virtual printer in a storage device;

(b) executing the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program;

(c) allocating the intermediate print data to said plurality of printers; and

and

(d) transmitting the intermediate print data respectively to said plurality of printers according to the allocation by said function (c) without any data conversion by the corresponding printer driver.

25

36. A computer readable recording medium in accordance with claim

35, wherein a predetermined unit of the allocation of the intermediate print data by said function (c) is each page of a document expressed by print data.

Art Unit: ***

37. (Amended) A computer readable recording medium in accordance with claim 35, wherein the intermediate print data obtained by said function (b) is temporarily registered as an intermediate print file in an external storage device.

38. A computer readable recording medium in accordance with claim 10 37, wherein said computer program causes the computer to attain the function of:

reading the intermediate print file registered in said external storage device in response to an external command and re-executing distributed printing of the intermediate print data in the intermediate print file with 15 said plurality of printers.

39. (Amended) A computer readable recording medium in accordance with claim 35, wherein said computer program further causes the computer to attain the functions of: (e) displaying an input window for distribution of the print data and setting various pieces of information required for distributing the print data into said plurality of printers, based on input data from an input device, where said function (c) allocates the intermediate print data, based on the various pieces of information set in said step (e); and (f) specifying the intermediate print data obtained by said function (b) as an intermediate print file and outputting the intermediate print file together with the various pieces of information set in said step (e) to an external storage device.

Art Unit: ***

09/980,210

40. A computer readable recording medium in which a computer
5 program used in a distributed printing control apparatus is recorded, said
distributed printing control apparatus distributing print data of interest,
which is generated by an application program and is to be printed, into a
plurality of printers and outputting the distributed print data to each of said
plurality of printers via a printer driver provided for said each printer,
10 said computer program causing a computer to attain at least one
function corresponding to the structure of a distributed printing control
apparatus in accordance with any one of claims 25 to 28 and 30.

41. A computer readable recording medium in which a computer
15 program used in a distributed printing control apparatus is recorded, said
distributed printing control apparatus distributing print data of interest,
which is generated by an application program and is to be printed, into a
plurality of printers and outputting the distributed print data to each of said
plurality of printers via a printer driver corresponding to a type of said each
20 printer, said computer program causing a computer to attain the functions of:
(a) specifying information on a virtual printer, and when said
plurality of printers are of an identical type, providing in advance a virtual
printer driver for specifying information on the identical type of said printers
in a storage device;
25 (b) executing the virtual printer driver to obtain intermediate print
data adequate for said virtual printer from said application program;

Art Unit: ***

(c) allocating the intermediate print data to said plurality of printers;

(d) determining whether or not said plurality of printers are of the identical type; and

(e) when it is determined that said plurality of printers are of the identical type, transmitting the intermediate print data respectively to said plurality of printers according to the allocation by said function (c) without any data conversion by the corresponding printer driver, and when it is determined that said plurality of printers are not of the identical type, transmitting the intermediate print data respectively to said plurality of printers according to the allocation by said function (c) with data conversion by the corresponding printer driver.

09980210
P. 13/14

42. A computer program used in a distributed printing control apparatus, said distributed printing control apparatus distributing print data of interest, which is generated by an application program and is to be printed, into a plurality of printers of an identical type and outputting the distributed print data to each of said plurality of printers via a printer driver provided for said each printer, said computer program causing a computer to attain the functions of:

(a) when said plurality of printers are of the identical type, providing in advance a virtual printer driver for specifying information on the identical type of said printers as information with regard to a virtual printer in a storage device;

(b) executing the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program;

(c) allocating the intermediate print data to said plurality of printers;

Art Unit: ***

and

(d) transmitting the intermediate print data respectively to said plurality of printers according to the allocation by said function (c) without any data conversion by the corresponding printer driver.

5

43. A computer program used in a distributed printing control apparatus, said distributed printing control apparatus distributing print data of interest, which is generated by an application program and is to be printed, into a plurality of printers and outputting the distributed print data to each
10 of said plurality of printers via a printer driver corresponding to a type of said each printer, said computer program causing a computer to attain the functions of:

(a) specifying information on a virtual printer, and when said plurality of printers are of an identical type, providing in advance a virtual
15 printer driver for specifying information on the identical type of said printers in a storage device;

(b) executing the virtual printer driver to obtain intermediate print data adequate for said virtual printer from said application program;

(c) allocating the intermediate print data to said plurality of printers;

20 (d) determining whether or not said plurality of printers are of the identical type; and

(e) when it is determined that said plurality of printers are of the identical type, transmitting the intermediate print data respectively to said plurality of printers according to the allocation by said function (c) without
25 any data conversion by the corresponding printer driver, and when it is determined that said plurality of printers are not of the identical type,

09980210-113001

Art Unit: ***

transmitting the intermediate print data respectively to said plurality of printers according to the allocation by said function (c) with data conversion by the corresponding printer driver.

5 44. A distributed printing control apparatus that groups print data of interest, which is to be printed, by a predetermined unit, specifies allocation of respective grouped parts of the print data to a plurality of printers as allocation information, and outputs the print data to said plurality of printers in a distributive manner based on the allocation information, said distributed
10 printing control apparatus comprising:

 a working status detection module that detects a current working status of a printer specified as a destination of distribution according to the allocation information; and

 a display control module that displays one window on a display device,
15 the window including at least a field showing the allocation information and another field showing the current working status detected by said working status detection module.

 45. A distributed printing control apparatus in accordance with claim
20 44, said distributed printing control apparatus further comprising:

 a first control module that causes said display control module to carry out a display with regard to a print job, while one unit of print data specified by the print job is either in distributed printing or in a waiting queue.

25 46. A distributed printing control apparatus in accordance with claim 45, said distributed printing control apparatus further comprising:

09980210-113001

Art Unit: ***

a second control module that causes said display control module to carry out a display with regard to the print job, while the distributed printing of the unit of print data specified by the print job is concluded.

- 5 47. A distributed printing control apparatus in accordance with claim 46, said distributed printing control apparatus further comprising a switch that is operated to alternatively change over between the display by said first control module and the display by said second control module.

48. (Amended) A distributed printing control apparatus in accordance with claim 46, wherein said second control module allocates an order of collection to the respective printers by considering a sequence of collected resulting prints and displays the allocation in the window.

49. (Amended) A distributed printing control apparatus in accordance with claim 46, wherein said second control module displays in the window a switch for activating another cycle of distributed printing after conclusion of one cycle of distributed printing.

50. (Amended) A distributed printing control apparatus in accordance with claim 44, wherein the allocation information with regard to multiple print jobs, each representing the print data, is simultaneously displayed in the window.

51. (Amended) A distributed printing control apparatus in accordance with claim 44, said distributed printing control apparatus comprising: a distribution information setting module that displays an input window on said display device and sets diverse pieces of information with regard to distribution of the print data, based on input data from an input device, wherein the allocation information is specified, based on the diverse pieces of information set by said distribution information setting module.

09/980,210-133001

Art Unit: ***

09/980,210-113003

52. A distributed printing control method that groups print data of
10 interest, which is to be printed, by a predetermined unit, specifies allocation
of respective grouped parts of the print data to a plurality of printers as
allocation information, and outputs the print data to said plurality of printers
in a distributive manner based on the allocation information, said distributed
printing control method comprising the steps of:

15 (a) detecting a current working status of a printer specified as a
destination of distribution according to the allocation information; and

(b) displaying one window on a display device, the window including
at least a field showing the allocation information and another field showing
the current working status detected in said step (a).

20

53. (Amended) A distributed printing control method that groups print data of
interest, which is to be printed, by a predetermined unit, specifies allocation of respective
grouped parts of the print data to a plurality of printers as allocation information, and outputs
the print data to said plurality of printers in a distributive manner based on the allocation
information, said distributed printing control method comprising at least one step
corresponding to the structure of a distributed printing control apparatus in accordance with
claim 45.

Art Unit: ***

09980210-112001

54. A computer readable recording medium in which a computer
5 program used in a distributed printing control apparatus is recorded, said
distributed printing control apparatus grouping print data of interest, which
is to be printed, by a predetermined unit, specifying allocation of respective
grouped parts of the print data to a plurality of printers as allocation
information, and outputting the print data to said plurality of printers in a
10 distributive manner based on the allocation information, said computer
program causing a computer to attain the functions of:

- (a) detecting a current working status of a printer specified as a
destination of distribution according to the allocation information; and
- (b) displaying one window on a display device, the window including
15 at least a field showing the allocation information and another field showing
the current working status detected by said function (a).

55. A computer readable recording medium in accordance with claim
54, wherein said computer program further causes the computer to attain the
20 function of:

- (c) carrying out a display with regard to a print job, while one unit of
print data specified by the print job is either in distributed printing or in a
waiting queue.

25 56. A computer readable recording medium in accordance with claim
55, wherein said computer program further causes the computer to attain the

Art Unit: ***

function of:

(d) carrying out a display with regard to the print job, while the distributed printing of the unit of print data specified by the print job is concluded.

57. (Amended) A computer readable recording medium in which a computer program used in a distributed printing control apparatus is recorded, said distributed printing control apparatus grouping print data of interest, which is to be printed, by a predetermined unit, specifying allocation of respective grouped parts of the print data to a plurality of printers as allocation information, and outputting the print data to said plurality of printers in a distributive manner based on the allocation information, said computer program causing a computer to attain at least one function corresponding to the structure of a distributed printing control apparatus in accordance with claim 47.

58. A computer program used in a distributed printing control apparatus, said distributed printing control apparatus grouping print data of interest, which is to be printed, by a predetermined unit, specifying allocation of respective grouped parts of the print data to a plurality of printers as allocation information, and outputting the print data to said plurality of printers in a distributive manner based on the allocation information, said computer program causing a computer to attain the functions of:

(a) detecting a current working status of a printer specified as a destination of distribution according to the allocation information; and

(b) displaying one window on a display device, the window including

Art Unit: ***

at least a field showing the allocation information and another field showing the current working status detected by said function (a).

59. A distributed printing control apparatus, comprising:

5 a printer specification module that specifies multiple printers as destinations of distribution among all printers connecting with said distributed printing control apparatus to allow data transmission; and

a distribution control module that outputs print data of interest, which is to be printed, in a distributive manner to the multiple printers specified by said printer specification module,

said distribution control module comprising:

a printer selection module that, when any trouble arises in any of the multiple printers specified by said printer specification module, selects one printer immediately available for printing among all the printers except the printer with the trouble; and

a troubled-time output module that outputs a distributed portion of the print data to the printer selected by said printer selection module as an alternative printer for the printer with the trouble.

20 60. A distributed printing control apparatus in accordance with claim 59, wherein said printer selection module comprises an identification module that identifies type of each printer to select a printer of an identical or similar type with or to a type of the printer with the trouble.

25 61. A distributed printing control apparatus in accordance with claim 60, said distributed printing control apparatus further comprising:

09580210.1A3701

Art Unit: ***

a performance information input module that receives information on performances of the respective printers from printer drivers provided for respective types of all the printers,

wherein said identification module comprises a type specification
5 module that specifies a printer of the identical or similar type, based on the information input into said performance information input module.

01

62. (Amended) A distributed printing control apparatus in accordance with claim 59, said distributed printing control apparatus further comprising: a monitor module that monitors occurrence of any trouble in each of the multiple printers specified by said printer specification module, wherein said distribution control module comprises an after-start-of-printing alternative control module, when said monitor module detects occurrence of any trouble in any of the multiple printers during a time period between a start of distributed output of the print data and completion of printing with each printer, outputs non-printed page data, which is included in a distributed portion of the print data output to the printer with the trouble, to the alternative printer.

63. A distributed printing control apparatus in accordance with claim 62, wherein said after-start-of-printing alternative control module outputs page data, which represents a message showing replacement of the printer, to the alternative printer.

35

Art Unit: ***

64. (Amended) A distributed printing control apparatus in accordance with claim 59, said distributed printing control apparatus further comprising: a monitor module that monitors occurrence of any trouble in each of the multiple printers specified by said printer specification module, wherein said distribution control module comprises a before-printing alternative control module, when said monitor module detects occurrence of any trouble in any of the multiple printers prior to a start of distributed output of the print data, outputs a portion of the print data, which is expected to be output to the printer with the trouble, to the alternative printer.

65. (Amended) A distributed printing control apparatus in accordance with claim 59, wherein said distribution control module comprises: a printer reselection module that, when any trouble arises in the alternative printer, selects one printer immediately available for printing among all the printers except the printer with the trouble; and a module that outputs a portion of the print data in a distributive manner to the printer selected by said printer reselection module as a new alternative printer.

20 66. A distributed printing control apparatus in accordance with claim 59, wherein said printer selection module comprises:

a candidate printer selection module that selects at least one printer that is of an identical or similar type with or to a type of the printer with the trouble and is immediately available for printing, among all the printers
25 except the printer with the trouble; and

an alternative printer selection module that selects one printer satisfying a predetermined condition out of the at least one printer selected by said candidate printer selection module.

Art Unit: ***

67. A distributed printing control apparatus in accordance with claim
5 66, wherein said printer selection module further comprises:

a selection method specification module that specifies whether the
selection of the alternative printer is carried out manually or automatically;

a manual printer selection module that, in response to specification of
the manual selection by said selection method specification module, displays
10 a data input window on a display device and selects one printer among all the
printers except the printer with the trouble, based on input data from an
input device according to the display of the window; and

a module that, in response to specification of the automatic selection
by said selection method specification module, activates said candidate
15 printer selection module and said alternative printer selection module.

68. (Amended) A distributed printing control apparatus in accordance with claim 66,
wherein said candidate printer selection module comprises: a first selection module that
selects a printer of an identical type with a type of the printer with the trouble, among all the
printers except the printer with the trouble; and a second selection module that, when no
printer is selected by said first selection module, selects a printer having a printing
performance close to that of the printer with the trouble, among all the printers except the
printer with the trouble.

Art Unit: ***

69. A distributed printing control apparatus in accordance with claim 68, wherein said distribution control module comprises:

5 a module that, when the printer selected by said second selection module is specified as the alternative printer, corrects the print data to make a resulting print obtained from the alternative printer substantially equivalent to a resulting print expected from the printer with the trouble.

70. (Amended) A distributed printing control apparatus in accordance with claim 66, wherein said candidate printer selection module comprises: a speed preference decision module that determines whether or not a speed preference mode is set for distributed printing; and an under-speed-preference-mode selection module that selects one available printer regardless of type of the printer, when said speed preference decision module gives an affirmative answer.

71. (Amended) A distributed printing control apparatus in accordance with claim 66, wherein said alternative printer selection module comprises: a module that selects a printer of a highest printing speed among the at least one printer selected by said candidate printer selection module.

72. (Amended) A distributed printing control apparatus in accordance claim 59, said distributed printing control apparatus further comprising: a display control module that displays a name of the printer selected by said alternative printer selection module on a display device.

Art Unit: ***

73. A distributed printing control apparatus in accordance with claim
5 72, said distributed printing control apparatus further comprising:

a module that causes said display control module to give a display
when the print data is either in distributed printing or in a waiting queue.

74. (Amended) A distributed printing control apparatus in accordance with claim 72,
said distributed printing control apparatus further comprising: a module that causes said
display control module to give a display when the distributed printing of the print data is
concluded.

75. (Amended) A distributed printing control apparatus in accordance with claim 59,
wherein said distribution control module comprises: a module that corrects the print data to
make a resulting print obtained from the alternative printer substantially similar to a resulting
print expected from the printer with the trouble, when the alternative printer is of a different
type from a type of the printer with the trouble.

76. A distributed printing control method, said method comprising the
steps of:

(a) specifying multiple printers as destinations of distribution among
25 all printers connecting to allow data transmission; and

(b) outputting print data of interest, which is to be printed, in a

Art Unit: ***

distributive manner to the multiple printers specified in said step (a),

said step (b) comprising the steps of:

- (b1) when any trouble arises in any of the multiple printers specified in said step (a), selecting one printer immediately available for printing
5 among all the printers except the printer with the trouble; and

(b2) outputting a distributed portion of the print data to the printer selected in said step (b1) as an alternative printer for the printer with the trouble.

- 10 77. A distributed printing control method in accordance with claim 76, wherein said step (b1) comprises the step of:

(b11) identifying type of each printer to select a printer of an identical or similar type with or to a type of the printer with the trouble.

78. (Amended) A distributed printing control method that outputs print data of interest, which is to be printed, to multiple printers in a distributive manner, said distributed printing control method comprising at least one step corresponding to the structure of a distributed printing control apparatus in accordance with claim 61.

79. A computer readable recording medium in which a computer program for controlling distributed printing is recorded, said computer program causing a computer to attain the functions of:

- (a) specifying multiple printers as destinations of distribution among
25 all printers connecting to allow data transmission; and

(b) outputting print data of interest, which is to be printed, in a

Art Unit: ***

distributive manner to the multiple printers specified by said function (a),
said function (b) comprising the functions of:

(b1) when any trouble arises in any of the multiple printers specified
by said function (a), selecting one printer immediately available for printing
5 among all the printers except the printer with the trouble; and

(b2) outputting a distributed portion of the print data to the printer
selected by said function (b1) as an alternative printer for the printer with
the trouble.

10 80. A computer readable recording medium in accordance with claim
79, wherein said function (b1) comprises the function of:

(b11) identifying type of each printer to select a printer of an identical
or similar type with or to a type of the printer with the trouble.

15 81. A computer readable recording medium in accordance with claim
80, wherein said computer program causes the computer to further attain the
function of:

(c) receiving information on performances of the respective printers
from printer drivers provided for respective types of all the printers,

20 said function (b11) specifying a printer of the identical or similar type,
based on the information input by said function (c).

82. (Amended) A computer readable recording medium in accordance with claim 79,
wherein said computer program causes the computer to further attain the function of: (d)

Art Unit: ***

monitoring occurrence of any trouble in each of the multiple printers specified by said function (a), said function (b) further comprising the function of: (b3) when occurrence of any trouble is detected by said function (d) in any of the multiple printers during a time period between a start of distributed output of the print data and completion of printing with each printer, outputting non-printed page data, which is included in a distributed portion of the print data output to the printer with the trouble, to the alternative printer.

83. (Amended) A computer readable recording medium in accordance with claim 82, wherein said function (b3) outputs page data, which represents a message showing replacement of the printer, to the alternative printer.

84. (Amended) A computer readable recording medium in accordance with claim 79, wherein said computer program causes the computer to further attain the function of: (d) monitoring occurrence of any trouble in each of the multiple printers specified by said function (a), said function (b) further comprising the function of: (b3) when occurrence of any trouble is detected by said function (d) in any of the multiple printers prior to a start of distributed output of the print data, outputting a portion of the print data, which is expected to be output to the printer with the trouble, to the alternative printer.

85. (Amended) A computer readable recording medium in accordance with claim 79, wherein said function (b) further comprises the functions of: (b3) when any trouble arises in the alternative printer, selecting one printer immediately available for printing among all the printers except the printer with the trouble; and (b4) outputting a portion of the print data in a distributive manner to the printer selected by said function (b3) as a new alternative printer.

Art Unit: ***

09980210-11300
00000000-00000000

86. A computer readable recording medium in accordance with claim 79, wherein said function (b1) comprises the functions of:

10 (b11) selecting at least one printer that is of an identical or similar type with or to a type of the printer with the trouble and is immediately available for printing, among all the printers except the printer with the trouble; and

(b12) selecting one printer satisfying a predetermined condition out of
15 the at least one printer selected by said function (b11).

87. A computer readable recording medium in accordance with claim 86, wherein said function (b1) comprises the functions of:

(b13) specifying whether the selection of the alternative printer is
20 carried out manually or automatically;

(b14) in response to specification of the manual selection by said function (b13), displaying a data input window on a display device and selecting one printer among all the printers except the printer with the trouble, based on input data from an input device according to the display of
25 the window; and

(b15) in response to specification of the automatic selection by said function (b13), activating said function (b11) and said function (b12).

Art Unit: ***

88. (Amended) A computer readable recording medium in accordance with claim 86, wherein said function (b11) comprises the functions of: (b111) selecting a printer of an identical type with a type of the printer with the trouble, among all the printers except the printer with the trouble; and (b112) when no printer is selected by said function (b111),

selecting a printer having a printing performance close to that of the printer with the trouble, among all the printers except the printer with the trouble.

89. A computer readable recording medium in accordance with claim 88, wherein said function (b) further comprises the function of:

15 when the printer selected by said function (b112) is specified as the alternative printer, correcting the print data to make a resulting print obtained from the alternative printer substantially equivalent to a resulting print expected from the printer with the trouble.

90. (Amended) A computer readable recording medium in accordance with claim 86, wherein said function (b11) further comprises the functions of: determining whether or not a speed preference mode is set for distributed printing; and selecting one available printer regardless of type of the printer, when it is determined that the speed preference mode is set.

91. (Amended) A computer readable recording medium in accordance with claim 86, wherein said function (b12) further comprises the function of: selecting a printer of a highest printing speed among the at least one printer selected by said function (b11).

92. (Amended) A computer readable recording medium in accordance with claim 79, wherein said computer program causes the computer to further attain the function of: (d) displaying a name of the printer selected by said function (b12) on a display device.

1122086612

Art Unit: ***

93. A computer readable recording medium in accordance with claim
15 92, wherein said computer program causes the computer to further attain the
function of:

activating said function (d) to give a display when the print data is
either in distributed printing or in a waiting queue.

94. (Amended) A computer readable recording medium in accordance with claim 92,
wherein said computer program causes the computer to further attain the function of:
activating said function (d) to give a display when the distributed printing of the print data is
concluded.

95. (Amended) A computer readable recording medium in accordance with claim 79,
wherein said function (b) further comprises the function of: correcting the print data to make
a resulting print obtained from the alternative printer substantially similar to a resulting print
expected from the printer with the trouble, when the alternative printer is of a different type
from a type of the printer with the trouble.